

ANTIQUE BUILDING SOLUTIONS

RECLAIMED BUILDING MATERIALS FROM THE SOURCE





SPECIFICATIONS & UNIQUE FEATURES

Species: Eastern White & Yellow Pine and Eastern Hemlock

Moisture

Historic Structures of Pennsylvania

Tones may range from tan to smokey amber to rich coffee brown. Reclaimed products

may exhibit an indefinite range of color variations.

Original Edge N/A

Dimensions:

Source:

Color:

Common Height | 5/8" & 3/4" Dimensions: Width | 3,4,5,6" | 4,5,6,7"

5,6,7,8" | 7,8,9,10"

Length | 2-12'

Rare/Custom Height | N/A **Dimensions:**

Width | Singular | 5, 7, 9"

Length | Singular or 12'+

For more products and photos visit: https://www.antiquebuildingsolutions.com Finish:

Content:

Knots:

Texture:

Voids:

Checks:

Original natural surface. Prefinish options are available.

Kiln dried 6-9% prior to shipment/milling.

> There are no restrictions on the presence of sound knots.

Various saw blade textures, animal

wear, beetle tracking, hardware & fastener impressions.

Chips & open knots with a diameter of up to 1" may be present. In some cases, larger voids may be included to maintain the board's length.

Discoloration: There is no limit to the amount of natural weather & mineral staining.

> Structural checks that do not compromise the plank's integrity after installation are permissible and tend to be more common as the material's width increases.

Antique Eastern Softwoods Original Face Solid Flooring

PENNSYLVANIA BARNWOOD

Mixed softwood flooring offers a variety of Eastern Hemlock, White Pine, and Yellow Pine that is carefully selected from centuries-old Pennsylvania barn walls and floors to maintain their history in contemporary homes. The "soft" in "softwood" speaks to the nature of these wood types and their tendency to keep a record of its past uses, marking bruises and chips with unparalleled appeal. As we like to think, the more softwood is used, the more beautiful it becomes.

Our old-growth softwood includes characteristics that cannot be found in modern softwood that is rapidly grown in tree farms. Centuries ago when our oldgrowth softwood was standing, the trees of the dense virgin forests were fighting over resources and growing at a much slower rate, ensuring tighter grain and durability unmatched by modern softwood.

TIPS FROM THE MILL

- If you are installing material 7" or wider, we suggest a nail and glue down. Bostik's BEST makes a great adhesive with a moisture vapor barrier.
- When including a pre-finish to any flooring. a micro bevel is required to keep the finish from standing proud on the edges.
- · Ask us about matching stair parts, registers, & transitions. We offer all standard nosing, returns, risers, stringers, & landing treads.

CUSTOM MILLING OPTIONS











NEED A QUOTE? WE'LL NEED SOME DETAILS.

- How much square footage do you need for this project?
 - We suggest 10-15% overage for waste & fall off.
- What widths & lengths do you need? Wider or singular widths and longer lengths possess a higher level of rarity & increased
- What thickness would you like?
 - 5/8" allows the mill to choose from a larger range of material, in certain instances, decreasing lead time.
- Would you like a milled profile or straight edge?
 - Straight Edge (SLR)
 - Tongue & Groove (T&G)
 - End-Matched (EM) *10" Max
 - Micro Bevel (MB)
 - Eased Edge (EE)
- How are you planning on shipping the material? Whether its LTL, Hot-shot or Full Truckload, we can assist with set-up.

Tip - You can create an original edge look by easing/texturizing the edges & naturally or lightly staining them.



