ANTIQUE BUILDING SOLUTIONS

RECLAIMED BUILDING MATERIALS FROM THE SOURCE



Antique Hardwoods
Hit & Miss Solid Flooring

PENNSYLVANIA BARNWOOD

Hit & Miss Mixed Hardwood offers a variety of Oak, Hickory, Walnut, Elm, Beech, Ash, and Maple that has been carefully chosen from centuries-old Pennsylvania barns and manicured to a more refined look from our mixed hardwood flooring. Hit & Miss or Skip-planing is a technique that allows us to lightly smooth reclaimed wood flooring panels, yet leave all of its texture, character, and history.

Our mixed hardwood variety provides flooring that displays different grain patterns, historic markings, and tones ranging from light to dark brown. More than our smooth-planed mixed hardwood flooring, this flooring still shows surface evidence of its historic age and former functional life. For those interested in flooring with character that readily presents itself, our Hit & Miss Mixed Hardwood will not disappoint.

SPECIFICATIONS & UNIQUE FEATURES

Species:	Old Growth American Oak, Hickory, Elm, Walnut, Beech, Ash & Maple
Source:	Historic Structures of Pennsylvania
Color:	Tones may range from whitish-brown to smokey amber to deep caramel. Reclaimed products may exhibit an indefinite range of color variations.
Original Edge Dimensions:	N/A
Common Dimensions:	Height | 5/8" & 3/4" Width | 3,4,5,6" | 4,5,6,7" 5,6,7,8" | 7,8,9,10" Length | 2-12'
Rare/Custom Dimensions:	Height | N/A Width | Singular | 5, 7, 9" Length | Singular or 12'+
Finish:	Unfinished. Pre-finish options are available.
Moisture Content:	Kiln dried 6–9% prior to shipment/milling.
Knots:	There are no restrictions on the presence of sound knots.
Texture:	Saw blade textures & smooth planed, beetle tracking, hardware & fastener impressions.
Voids:	Chips & open knots with a diameter of up to 1" may be present. In some cases, larger voids may be included to maintain the board's length.
Discoloration:	There is no limit to the amount of natural weather & mineral staining.
Checks:	Structural checks that do not compromise the plank's integrity after installation are permissible and tend to be more common as the material's width increases.

For more products and photos visit:
https://www.antiquebuildingsolutions.com

TIPS FROM THE MILL

- If you are installing material 7" or wider, we suggest a nail and glue down. Bostik's BEST makes a great adhesive with a moisture vapor barrier.
- When including a pre-finish to any flooring, a micro bevel is required to keep the finish from standing proud on the edges.
- Ask us about matching stair parts, registers, & transitions. We offer all standard nosing, returns, risers, stringers, & landing treads.

CUSTOM MILLING OPTIONS

NEED A QUOTE? WE'LL NEED SOME DETAILS.

- How much square footage do you need for this project?
  - We suggest 10-15% overage for waste & fall off.
- What widths & lengths do you need? Wider or singular widths and longer lengths possess a higher level of rarity & increased investment.
- What thickness would you like?
  - 5/8" allows the mill to choose from a larger range of material, in certain instances, decreasing lead time.
- Would you like a milled profile or straight edge?
  - Straight Edge (SLR)
  - Tongue & Groove (T&G)
  - End-Matched (EM) *10" Max
  - Micro Bevel (MB)
  - Eased Edge (EE)
- How are you planning on shipping the material? LTL, Hot-shot & Full truck load. We can assist with set-up.

Tip - You can create a singular board look by easing/texturizing the edges.

OFFICE | 814.482.0800 SHOWROOM | 3149 NITTANY VALLEY DR, HOWARD, PA 16841 WEBSITE | WWW.ANTIQUEBUILDINGSOLUTIONS.COM