



# ANTIQUE BUILDING SOLUTIONS

## RECLAIMED BUILDING MATERIALS FROM THE SOURCE



### Antique American White Oak Clean Face Solid Flooring

PENNSYLVANIA BARNWOOD

Reclaimed White Oak flooring is distinguished unlike any other type of flooring—its warm light brown patina and distinctive, varied grain patterns can only be found in old growth oak. The coloration of each panel is filled with golden hues that vary from light tans to smokey amber. The slow aging and drying process of this wood over time also ensures a density and durability in White Oak that is unmatched.

White Oak stands as the timeless flooring classic, cherished by homeowners and builders alike for its understated beauty and unparalleled strength. It continues to reign as the most popular choice for flooring, offering a perfect combination that withstands the test of time.

#### SPECIFICATIONS & UNIQUE FEATURES

Species:	Old Growth American White Oak	Finish:	Unfinished. Pre-finish options are available.
Source:	Cut from beams in historic structures of Pennsylvania	Moisture Content:	Kiln dried 6–9% prior to shipment/milling.
Color:	Tones may range from light tan to grey to smokey brown. Reclaimed products may exhibit an indefinite range of color variations.	Knots:	There are no restrictions on the presence of sound knots.
Original Edge Dimensions:	N/A	Texture:	Smooth with fastener impressions, checks, beetle tracking, knot and peg/bolt voids.
Common Dimensions:	Height   5/8" & 3/4" Width   3,4,5,6"   4,5,6,7" 5,6,7,8"   7,8,9,10" Length   2-12'	Voids:	Chips & open knots with a diameter of up to 1" may be present. In some cases, larger voids may be included to maintain the board's length.
Rare/Custom Dimensions:	Height   N/A Width   Singular   5, 7, 9" Length   Singular or 12'+	Discoloration:	There is no limit to the amount of natural weather & mineral staining.
		Checks:	Structural checks that do not compromise the plank's integrity after installation are permissible and tend to be more common as the material's width increases.

For more products and photos visit:  
<https://www.antiquebuildingsolutions.com>

#### TIPS FROM THE MILL

- If you are installing material 7" or wider, we suggest a nail and glue down. Bostik's BEST makes a great adhesive with a moisture vapor barrier.
- When including a pre-finish to any flooring, a micro bevel is required to keep the finish from standing proud on the edges.
- Ask us about matching stair parts, registers, & transitions. We offer all standard nosing, returns, risers, stringers, & landing treads.

#### CUSTOM MILLING OPTIONS



#### NEED A QUOTE? WE'LL NEED SOME DETAILS.

- How much square footage do you need for this project?
  - We suggest 10-15% overage for waste & fall off.
- What widths & lengths do you need? Wider or singular widths and longer lengths possess a higher level of rarity & increased investment.
- What thickness would you like?
  - 5/8" allows the mill to choose from a larger range of material, increasing quality & decreasing lead time.
- Would you like a milled profile or straight edge?
  - Straight Edge (SLR)
  - Tongue & Groove (T&G)
  - End-Matched (EM) \*10" Max
  - Micro Bevel (MB)
  - Eased Edge (EE)
- How are you planning on shipping the material? Whether its LTL, Hot-shot or Full Truckload, we can assist with set-up.

**Tip** - You can create a singular board look by easing/texturizing the edges.

**Did you know?** These planks were cut from barn beams harvested by hand in the 17-1800's. Most of them starting from seedlings in the 14-1500's!