

ANTIQUE BUILDING SOLUTIONS

RECLAIMED BUILDING MATERIALS FROM THE SOURCE





SPECIFICATIONS & UNIQUE FEATURES

Species: Eastern Yellow Pine

Cut from beams in historic

structures of Pennsylvania

Tones may range from tan to yellow to amber brown. Reclaimed products may exhibit an indefinite range of

color variations.

Original Edge N/A Dimensions:

Source:

Color:

Common

Height | 5/8" & 3/4" Dimensions: Width | 3,4,5,6" | 4,5,6,7"

5,6,7,8" | 7,8,9,10" Length | 2-12'

Rare/Custom Height | N/A Dimensions: Width | Singular | 5, 7, 9"

Length | Singular or 12'+

For more products and photos visit: https://www.antiquebuildingsolutions.com Finish:

Moisture

Content:

Knots:

Texture:

Voids:

Checks:

Discoloration:

Unfinished. Pre-finish options are available.

Kiln dried 6-9% prior to shipment/milling.

There are no restrictions on the presence of sound knots.

Smooth with fastener impressions,

checks, beetle tracking, knot and

peg/bolt voids.

Chips & open knots with a diameter of up to 1" may be present. In some cases, larger voids may be included to maintain the board's length.

There is no limit to the amount of

natural weather & mineral staining.

Structural checks that do not compromise the plank's integrity after installation are permissible and tend to be more common as the material's width increases.

Eastern Yellow Pine Clean Face Solid Flooring

PENNSYLVANIA BARNWOOD

The color and character of our Eastern Yellow Pine flooring is the result of hundreds of years of aging. Yellow Pine is defined by pronounced grain patterns with notable, swirling rings, and is known for tones of rich yellow, amber, and red. Our yellow pine flooring has even more character than most, as it is reclaimed from historic siding, flooring, and beams.

Our old-growth softwood includes characteristics that cannot be found in modern softwood that is rapidly grown in tree farms. Centuries ago when our old-growth softwood was standing, the trees of the dense virgin forests were fighting over resources and growing at a much slower rate, ensuring tighter grain and durability unmatched by modern softwood.

TIPS FROM THE MILL

- If you are installing material 7" or wider, we suggest a nail and glue down. Bostik's BEST makes a great adhesive with a moisture vapor barrier.
- When including a pre-finish to any flooring. a micro bevel is required to keep the finish from standing proud on the edges.
- · Ask us about matching stair parts, registers, & transitions. We offer all standard nosing, returns, risers, stringers, & landing treads.

CUSTOM MILLING OPTIONS











NEED A QUOTE? WE'LL NEED SOME DETAILS.

- How much square footage do you need for this project?
 - We suggest 10-15% overage for waste & fall off.
- What widths & lengths do you need? Wider or singular widths and longer lengths possess a higher level of rarity & increased
- What thickness would you like?
 - 5/8" allows the mill to choose from a larger range of material, decreasing lead time.
- Would you like a milled profile or straight edge?
 - Straight Edge (SLR)
 - Tongue & Groove (T&G)
 - End-Matched (EM) *10" Max
 - Micro Bevel (MB)
 - Eased Edge (EE)
- How are you planning on shipping the material? Whether its LTL. Hotshot or Full Truckload, we can assist with set-up.

Tip - You can create a singular board look by easing/texturizing the edges.

Did you know? These planks were cut from barn beams harvested by hand in the 17-1800's. Most of them starting from seedlings in the 14-1500's!